SAFETY DATA SHEET

1. Identification

Product number 1000016704

Product identifier B58001 KONK TOTAL RELEASE FUMIGATOR - 150g

ACUITY HOLDINGS INC. dba AMREP Company information

11627 178 STREET NW

EDMONTON, AB T5S 1N6 Canada

General Assistance 1-905 669-9876 Company phone

1-866-836-8855 **Emergency telephone US Emergency telephone outside**

1-952-852-4646

US

01 Version #

Recommended use **PESTICIDE Recommended restrictions** None known.

2. Hazard(s) identification

Category 1 **Physical hazards** Flammable aerosols Skin corrosion/irritation **Health hazards** Category 2

> Specific target organ toxicity, single exposure Category 3 narcotic effects

Aspiration hazard Category 1

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation. **Hazard statement**

May cause drowsiness or dizziness.

Precautionary statement

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open Prevention

flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area.

Wear protective gloves.

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash Response

with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention.

Category 1

Take off contaminated clothing and wash before reuse.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from

sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international regulations. Disposal

Environmental hazards Hazardous to the aquatic environment, acute Category 1

Hazardous to the aquatic environment,

long-term hazard

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Naphtha, (Petroleum), Hydrotreated Light		64742-49-0	20 - 40
Propane		74-98-6	20 - 40
n-Heptane		142-82-5	10 - 20
Isopropyl Alcohol		67-63-0	2.5 - 10
Methylcyclohexane		108-87-2	1 - 2.5
Piperonyl Butoxide		51-03-6	1 - 2.5
Pyrethrins		8003-34-7	0.1 - 1
Other components below reportable le	evels		1 - 2.5

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTER or doctor/physician if you feel unwell.

Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get Skin contact

medical advice/attention. Wash contaminated clothing before reuse.

Headache. Nausea, vomiting. Skin irritation. May cause redness and pain.

Rinse with water. Get medical attention if irritation develops and persists. Eye contact

Call a physician or poison control center immediately. Do not induce vomiting. Ingestion

Most important

symptoms/effects, acute and

delayed Indication of immediate

medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation.

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness.

Symptoms may be delayed.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Foam. Powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters

Fire fighting

equipment/instructions

Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do Specific methods

not breathe fumes.

General fire hazards Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent entry into waterways, sewer, basements or confined areas. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes, skin, and clothing. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

TWA 200 ppm Methylcyclohexane (CAS TWA 400 ppm 108-87-2) n-Heptane (CAS 142-82-5) STEL 500 ppm TWA 400 ppm	US. OSHA Table Z-1 Limits for Air Components	Type	Value
Methylcyclohexane (CAS 108-87-2) PEL 2000 mg/m3 108-87-2) 500 ppm n-Heptane (CAS 142-82-5) PEL 2000 mg/m3 500 ppm 500 ppm Propane (CAS 74-98-6) PEL 1800 mg/m3 1000 ppm 1000 ppm Pyrethrins (CAS 8003-34-7) PEL 5 mg/m3 US. ACGIH Threshold Limit Values Components Type Value Isopropyl Alcohol (CAS STEL 400 ppm Image: Street of the street of		PEL	Č
108-67-2 500 ppm 108-67-2 500 ppm 109 ppm 109 ppm 100 ppm 100 ppm 100 ppm 100 ppm 100 ppm 100 ppm 10			·
n-Heptane (CAS 142-82-5) PEL 2000 mg/m3 500 ppm Propane (CAS 74-98-6) PEL 18800 mg/m3 1000 ppm Pyrethrins (CAS 8003-34-7) PEL 5 mg/m3 US. ACGIH Threshold Limit Values Components Type Value Sopropyl Alcohol (CAS 67-63-0) TWA 200 ppm Methylcyclohexane (CAS 100 ppm TWA 400 ppm 108-87-2) n-Heptane (CAS 142-82-5) TWA 108 NIOSH: Pocket Guide to Chemical Hazards Components Type Value Sopropyl Alcohol (CAS STEL 500 ppm TWA 400 ppm 108-87-2) TWA 5 mg/m3 US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Sopropyl Alcohol (CAS STEL 1225 mg/m3 67-63-0) TWA 980 mg/m3 400 ppm Methylcyclohexane (CAS 100 ppm 1WA		PEL	2000 mg/m3
Propane (CAS 74-98-6) PEL 1800 mg/m3 1000 ppm			500 ppm
Propane (CAS 74-98-6) PEL 1800 mg/m3 1000 ppm Pyrethrins (CAS 8003-34-7) PEL 5 mg/m3 US. ACGIH Threshold Limit Values Components Type Value Isopropyl Alcohol (CAS 67-63-0) TWA 200 ppm Methylcyclohexane (CAS 142-82-5) TWA 400 ppm 108-87-2) TWA 400 ppm Pyrethrins (CAS 8003-34-7) TWA 5 mg/m3 US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Isopropyl Alcohol (CAS 67-63-0) STEL 1225 mg/m3 Methylcyclohexane (CAS 142-82-5) TWA 980 mg/m3 400 ppm Methylcyclohexane (CAS 142-82-5) TWA 1600 mg/m3 400 ppm NHEAD 1600 mg/m3 1800 mg/m3 180	n-Heptane (CAS 142-82-5)	PEL	2000 mg/m3
Note			500 ppm
Pyrethrins (CAS 8003-34-7) PEL 5 mg/m3 US. ACGIH Threshold Limit Values Components Type Value Isopropyl Alcohol (CAS 67-63-0) STEL 400 ppm Methylcyclohexane (CAS 108-87-2) TWA 200 ppm Methylcyclohexane (CAS 142-82-5) STEL 500 ppm 1WA 400 ppm Pyrethrins (CAS 8003-34-7) TWA 5 mg/m3 US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Isopropyl Alcohol (CAS 67-63-0) STEL 1225 mg/m3 67-63-0) 500 ppm 500 ppm Methylcyclohexane (CAS 108-87-2) TWA 980 mg/m3 400 ppm Methylcyclohexane (CAS 142-82-5) TWA 1600 mg/m3 440 ppm n-Heptane (CAS 142-82-5) Ceilling 1800 mg/m3 440 ppm n-Heptane (CAS 74-98-6) TWA 350 mg/m3 85 ppm Propane (CAS 74-98-6) TWA 1800 mg/m3	Propane (CAS 74-98-6)	PEL	1800 mg/m3
Pyrethrins (CAS 8003-34-7) PEL 5 mg/m3 US. ACGIH Threshold Limit Values Components Type Value Isopropyl Alcohol (CAS 67-63-0) STEL 400 ppm Methylcyclohexane (CAS 108-87-2) TWA 200 ppm Methylcyclohexane (CAS 142-82-5) TWA 400 ppm 108-87-2) TWA 400 ppm Pyrethrins (CAS 8003-34-7) TWA 5 mg/m3 US. NIOSH: Pocket Guide to Chemical Hazards Components Value Isopropyl Alcohol (CAS 67-63-0) STEL 1225 mg/m3 67-63-0) TWA 980 mg/m3 400 ppm Methylcyclohexane (CAS 108-87-2) TWA 1600 mg/m3 Methylcyclohexane (CAS 142-82-5) Ceiling 1800 mg/m3 440 ppm n-Heptane (CAS 142-82-5) Ceiling 1800 mg/m3 440 ppm propane (CAS 74-98-6) TWA 1800 mg/m3 185 ppm Propane (CAS 74-98-6) TWA 1800 mg/m3			1000 ppm
Components Type Value Isopropyl Alcohol (CAS 67-63-0) STEL 400 ppm 67-63-0) TWA 200 ppm Methylcyclohexane (CAS 1W2-82-5) TWA 400 ppm 108-87-2) STEL 500 ppm 500 ppm 1WA 400 ppm 400 ppm Pyrethrins (CAS 8003-34-7) TWA 5 mg/m3 US. NIOSH: Pocket Guide to Chemical Hazards Components Components Type Value Isopropyl Alcohol (CAS 67-63-0) STEL 1225 mg/m3 500 ppm TWA 980 mg/m3 400 ppm 400 ppm Methylcyclohexane (CAS 142-82-5) TWA 1600 mg/m3 1600 mg/m3 440 ppm 108-87-2) 400 ppm n-Heptane (CAS 142-82-5) Ceiling 1800 mg/m3 440 ppm TWA 350 mg/m3 85 ppm 85 ppm Propane (CAS 74-98-6) TWA 1800 mg/m3	Pyrethrins (CAS 8003-34-7)	PEL	
Components Type Value Isopropyl Alcohol (CAS 67-63-0) STEL 400 ppm 67-63-0) TWA 200 ppm Methylcyclohexane (CAS 1W2-82-5) TWA 400 ppm 108-87-2) STEL 500 ppm 500 ppm 1WA 400 ppm 400 ppm Pyrethrins (CAS 8003-34-7) TWA 5 mg/m3 US. NIOSH: Pocket Guide to Chemical Hazards Components Components Type Value Isopropyl Alcohol (CAS 67-63-0) STEL 1225 mg/m3 500 ppm TWA 980 mg/m3 400 ppm 400 ppm Methylcyclohexane (CAS 142-82-5) TWA 1600 mg/m3 1600 mg/m3 440 ppm 108-87-2) 400 ppm n-Heptane (CAS 142-82-5) Ceiling 1800 mg/m3 440 ppm TWA 350 mg/m3 85 ppm 85 ppm Propane (CAS 74-98-6) TWA 1800 mg/m3	US ACGIH Threshold Limit Values		
Isopropyl Alcohol (CAS STEL 400 ppm			Value
67-63-0) TWA 200 ppm Methylcyclohexane (CAS TWA 400 ppm 108-87-2) n-Heptane (CAS 142-82-5) STEL 500 ppm Pyrethrins (CAS 8003-34-7) TWA 400 ppm Pyrethrins (CAS 8003-34-7) TWA 5 mg/m3 US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Isopropyl Alcohol (CAS STEL 1225 mg/m3 67-63-0) TWA 980 mg/m3 400 ppm Methylcyclohexane (CAS TWA 1600 mg/m3 108-87-2) n-Heptane (CAS 142-82-5) Ceiling 1800 mg/m3 100 ppm TWA 350 mg/m3 100 mg/m3		-	
Methylcyclohexane (CAS 108-87-2) TWA 400 ppm n-Heptane (CAS 142-82-5) STEL 500 ppm TWA 400 ppm Pyrethrins (CAS 8003-34-7) TWA 5 mg/m3 US. NIOSH: Pocket Guide to Chemical Hazards Components Value Isopropyl Alcohol (CAS 67-63-0) STEL 1225 mg/m3 TWA 980 mg/m3 400 ppm Methylcyclohexane (CAS 170 ppm TWA 1600 mg/m3 Methylcyclohexane (CAS 142-82-5) Ceiling 1800 mg/m3 440 ppm n-Heptane (CAS 142-82-5) Ceiling 1800 mg/m3 85 ppm Propane (CAS 74-98-6) TWA 1800 mg/m3	Isopropyl Alcohol (CAS 67-63-0)	STEL	400 ppm
108-87-2) n-Heptane (CAS 142-82-5)		TWA	200 ppm
TWA 400 ppm Pyrethrins (CAS 8003-34-7) TWA 5 mg/m3 US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Isopropyl Alcohol (CAS 574-98-6) TWA 500 ppm TWA 500 ppm 500 ppm 500 ppm 500 ppm 980 mg/m3 400 ppm 1600 mg/m3 400 ppm 1800 mg/m3 440 ppm 1800 mg/m3 440 ppm 1800 mg/m3		TWA	400 ppm
Pyrethrins (CAS 8003-34-7) TWA 5 mg/m3 US. NIOSH: Pocket Guide to Chemical Hazards Type Value Isopropyl Alcohol (CAS 67-63-0) STEL 1225 mg/m3 500 ppm 500 ppm TWA 980 mg/m3 400 ppm 400 ppm n-Heptane (CAS 142-82-5) Ceiling 1800 mg/m3 440 ppm 440 ppm TWA 350 mg/m3 45 ppm 85 ppm Propane (CAS 74-98-6) TWA 1800 mg/m3	,	STEL	500 ppm
Pyrethrins (CAS 8003-34-7) TWA 5 mg/m3 US. NIOSH: Pocket Guide to Chemical Hazards Type Value Isopropyl Alcohol (CAS 67-63-0) STEL 1225 mg/m3 500 ppm 500 ppm TWA 980 mg/m3 400 ppm 400 ppm n-Heptane (CAS 142-82-5) Ceiling 1800 mg/m3 440 ppm 440 ppm TWA 350 mg/m3 45 ppm 85 ppm Propane (CAS 74-98-6) TWA 1800 mg/m3	. ,	TWA	400 ppm
Components Type Value Isopropyl Alcohol (CAS 67-63-0) STEL 1225 mg/m3 500 ppm 500 ppm TWA 980 mg/m3 400 ppm 400 ppm n-Heptane (CAS 142-82-5) Ceiling 1800 mg/m3 440 ppm 440 ppm TWA 350 mg/m3 85 ppm Propane (CAS 74-98-6) TWA 1800 mg/m3	Pyrethrins (CAS 8003-34-7)	TWA	
Components Type Value Isopropyl Alcohol (CAS 67-63-0) STEL 1225 mg/m3 500 ppm 500 ppm TWA 980 mg/m3 400 ppm 400 ppm n-Heptane (CAS 142-82-5) Ceiling 1800 mg/m3 440 ppm 440 ppm TWA 350 mg/m3 85 ppm Propane (CAS 74-98-6) TWA 1800 mg/m3	US. NIOSH: Pocket Guide to Chem	nical Hazards	
67-63-0) TWA 500 ppm 980 mg/m3 400 ppm Methylcyclohexane (CAS 108-87-2) N-Heptane (CAS 142-82-5) Ceiling TWA 400 ppm 1800 mg/m3 440 ppm TWA 350 mg/m3 85 ppm Propane (CAS 74-98-6) TWA 1800 mg/m3			Value
TWA 980 mg/m3 400 ppm Methylcyclohexane (CAS TWA 1600 mg/m3 108-87-2) 400 ppm n-Heptane (CAS 142-82-5) Ceiling 1800 mg/m3 440 ppm TWA 350 mg/m3 85 ppm Propane (CAS 74-98-6) TWA 1800 mg/m3		STEL	1225 mg/m3
TWA 980 mg/m3 400 ppm Methylcyclohexane (CAS TWA 1600 mg/m3 108-87-2) 400 ppm n-Heptane (CAS 142-82-5) Ceiling 1800 mg/m3 440 ppm TWA 350 mg/m3 85 ppm Propane (CAS 74-98-6) TWA 1800 mg/m3	07-03-0)		500 ppm
Methylcyclohexane (CAS TWA 1600 mg/m3 108-87-2) n-Heptane (CAS 142-82-5) Ceiling 1800 mg/m3 440 ppm 100 ppm		Τ\Λ/Λ	·
Methylcyclohexane (CAS TWA 1600 mg/m3 108-87-2) 400 ppm n-Heptane (CAS 142-82-5) Ceiling 1800 mg/m3 440 ppm 440 ppm TWA 350 mg/m3 85 ppm Propane (CAS 74-98-6) TWA 1800 mg/m3		IVVA	<u> </u>
108-87-2) n-Heptane (CAS 142-82-5) Ceiling 1800 mg/m3 440 ppm TWA 350 mg/m3 85 ppm Propane (CAS 74-98-6) TWA 1800 mg/m3	Mathylayalahayana (CAC	T\A/A	·
n-Heptane (CAS 142-82-5) Ceiling 1800 mg/m3 440 ppm TWA 350 mg/m3 85 ppm Propane (CAS 74-98-6) TWA 1800 mg/m3		IWA	· ·
440 ppm TWA 350 mg/m3 85 ppm Propane (CAS 74-98-6) TWA 1800 mg/m3		0 "	·
TWA 350 mg/m3 85 ppm Propane (CAS 74-98-6) TWA 1800 mg/m3	n-Heptane (CAS 142-82-5)	Ceiling	
Propane (CAS 74-98-6) TWA 85 ppm 1800 mg/m3			··
Propane (CAS 74-98-6) TWA 1800 mg/m3		TWA	
1000 ppm	Propane (CAS 74-98-6)	TWA	
			1000 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

 Components
 Type
 Value

 Pyrethrins (CAS 8003-34-7)
 TWA
 5 mg/m3

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Isopropyl Alcohol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*

^{* -} For sampling details, please see the source document.

Appropriate engineering

controls

Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection If contact is likely, safety glasses with side shields are recommended.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other Wear appropriate chemical resistant clothing.

Respiratory protection If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an

air-supplied respirator.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Gas.
Form Aerosol.
Color Not available.
Odor Not available.
Odor threshold Not available.
PH Not available.
Melting point/freezing point Not available.

Initial boiling point and boiling

range

203 °F (95 °C) estimated

Flash point -38.4 °F (-39.1 °C) estimated

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

1.3 % estimated

(%)

Flammability limit - upper

8.4 % estimated

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 513.03 °F (267.24 °C) estimated

Decomposition temperatureNot available. **Viscosity**Not available.

Other information

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

Specific gravity 0.659 estimated

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materialsStrong oxidizing agents. Isocyanates. Chlorine.Hazardous decompositionNo hazardous decomposition products are known.

products

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause drowsiness and dizziness. Headache. Nausea, vomiting.

Skin contact Causes skin irritation.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious

chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness.

Headache. Nausea, vomiting. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways. Narcotic effects.

Components	Species	Test Results
Icopropyl Alcohol (CAS 67 63 0)		

Isopropyi Alcohol (CAS 67-63-0)

Acute

Dermal

LD50 Rabbit 16.4 ml/kg, 24 Hours

Inhalation

LC50 Rat > 10000 ppm, 6 Hours

Oral

LD50 Rat 5.84 g/kg

Methylcyclohexane (CAS 108-87-2)

Acute Dermal

LD50 Rabbit > 2000 mg/kg, 24 Hours

Inhalation

Vapor

LC100 Rabbit 59.9 mg/l

LC50 Dog > 4071 ppm, If <1L: Consumer Commodity

Hours

> 16.3 mg/l, If <1L: Consumer Commodity

Hours

Mouse > 6564 ppm, If <1L: Consumer Commodity

Hours

> 26.3 mg/l, If <1L: Consumer Commodity

Hours

Components	Species	Test Results
	Rat	> 6564 ppm, If <1L: Consumer Commodity Hours
		> 26.3 mg/l, If <1L: Consumer Commodity Hours
LC50	Rat	16 mg/l, 4 Hours
Naphtha, (Petroleum), Hydro	otreated Light (CAS 64742-49-0)	
<u>Acute</u>		
Dermal		
LD50	Guinea pig; Rabbit	> 9.4 ml/kg, 24 Hours
	Rabbit	> 1900 mg/kg, 24 Hours
Inhalation		
LC50	Rat	> 5000 mg/m3, 4 Hours
		> 4980 mg/m3
		> 4980 mg/m3, 4 Hours
		> 4.96 mg/l, 4 Hours
		13700 ppm, 4 Hours
Oral		10700 ppm, 1110aid
LD50	Rat	4820 mg/kg
n-Heptane (CAS 142-82-5)		<u></u>
Acute		
<u>Prouto</u> Dermal		
LD50	Rabbit	> 2000 mg/kg, 24 Hours
Inhalation		3 3
LC50	Rat	> 29.29 mg/l, 4 Hours
Oral		•
LD50	Rat	> 5000 mg/kg
Piperonyl Butoxide (CAS 51-	03-6)	
Acute	,	
Dermal		
LD50	-	> 2000 mg/kg
Inhalation		
LC50	Rat	> 5.2 mg/l, 4 Hours
Oral		
LD50	Rat	> 2000 mg/kg
Propane (CAS 74-98-6)		
<u>Acute</u>		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
		658 mg/l/4h
		ŭ

^{*} Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Piperonyl Butoxide (CAS 51-03-6)

3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

May cause drowsiness and dizziness.

single exposure

Specific target organ toxicity -

repeated exposure

Components

Not classified.

Aspiration hazard

May be fatal if swallowed and enters airways.

Species

12. Ecological information

Ecotoxicity Very toxic to aquatic life with long lasting effects.

		- p	
Isopropyl Alcohol (CA	S 67-63-0)		
Aquatic			
Algae	IC50	Algae	1000.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia	13299 mg/L, 48 Hours
Fish	LC50	Bluegill (Lepomis macrochirus)	> 1400 mg/l, 96 hours
Methylcyclohexane (C	CAS 108-87-2)		
Aquatic			
Fish	LC50	Striped bass (Morone saxatilis)	5.8 mg/l, 96 hours
n-Heptane (CAS 142-	82-5)		
Aquatic			
Fish	LC50	Mozambique tilapia (Tilapia mossambica)	375 mg/l, 96 hours
Piperonyl Butoxide (C	AS 51-03-6)		
Aquatic			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	0.0027 - 0.0043 mg/l, 96 hours
Pyrethrins (CAS 8003	3-34-7)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia)	0.018 - 0.032 mg/l, 48 hours
Fish	LC50	Brown trout (Salmo trutta)	0.0165 - 0.0229 mg/l, 96 hours

Test Results

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Isopropyl Alcohol0.05Methylcyclohexane3.61n-Heptane4.66Piperonyl Butoxide4.75Propane2.36

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

^{*} Estimates for product may be based on additional component data not shown.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

14. Transport information

DOT

UN1950 **UN** number

UN proper shipping name Transport hazard class(es) Aerosols, flammable, (each not exceeding 1 L capacity)

Class 2.1

Subsidiary risk Label(s) 2.1

Packing group Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Special provisions Packaging exceptions 306 Packaging non bulk None Packaging bulk None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking.

IATA

UN1950 **UN** number

UN proper shipping name

Transport hazard class(es)

Aerosols, flammable

Class 2.1 Subsidiary risk 2.1 Label(s)

Packing group Not applicable.

Environmental hazards Yes **ERG Code**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

Packaging Exceptions LTD QTY

IMDG

UN1950 **UN** number UN proper shipping name **AEROSOLS**

Transport hazard class(es)

Class 2.1 Subsidiary risk Label(s) 2.1

Packing group Not applicable. **Environmental hazards**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Packaging Exceptions Transport in bulk according to Annex II of MARPOL 73/78 and

Not applicable.

LTD QTY

the IBC Code

DOT



IATA; IMDG



Marine pollutant



General information IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Pyrethrins (CAS 8003-34-7) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Piperonyl Butoxide	51-03-6	1 - 2.5

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Propane (CAS 74-98-6)

Safe Drinking Water Act

(SDWA)

Not regulated.

FIFRA Information

This chemical is a pesticide product registered by the United States Environmental Protection Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS), and for workplace labels of non-pesticide chemicals. The pesticide label also includes other important information, including directions for use.

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

Isopropyl Alcohol (CAS 67-63-0)

Naphtha, (Petroleum), Hydrotreated Light (CAS 64742-49-0)

US. Massachusetts RTK - Substance List

Isopropyl Alcohol (CAS 67-63-0)

Methylcyclohexane (CAS 108-87-2)

n-Heptane (CAS 142-82-5)

Propane (CAS 74-98-6)

Pyrethrins (CAS 8003-34-7)

US. New Jersey Worker and Community Right-to-Know Act

Isopropyl Alcohol (CAS 67-63-0)

Methylcyclohexane (CAS 108-87-2)

n-Heptane (CAS 142-82-5)

Piperonyl Butoxide (CAS 51-03-6)

Propane (CAS 74-98-6)

Pyrethrins (CAS 8003-34-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Isopropyl Alcohol (CAS 67-63-0)

Methylcyclohexane (CAS 108-87-2)

n-Heptane (CAS 142-82-5)

Propane (CAS 74-98-6)

Pyrethrins (CAS 8003-34-7)

US. Rhode Island RTK

Isopropyl Alcohol (CAS 67-63-0)

Piperonyl Butoxide (CAS 51-03-6)

Propane (CAS 74-98-6)

Pyrethrins (CAS 8003-34-7)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

SDS US

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Benzene (CAS 71-43-2) Listed: February 27, 1987 Ethyl Benzene (CAS 100-41-4) Listed: June 11, 2004

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Inventory name

Benzene (CAS 71-43-2) Listed: December 26, 1997 Toluene (CAS 108-88-3) Listed: January 1, 1991

US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

Benzene (CAS 71-43-2) Listed: December 26, 1997

Australian Inventory of Chemical Substances (AICS)

International Inventories

Australia

Country(s) or region

Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances	No

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 05-26-2017

Version # 01

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Revision information Product and Company Identification: Alternate Trade Names

Product name: B58001 KONK TOTAL RELEASE FUMIGATOR - 150g

Product #: 1000016704 Version #: 01 Issue date: 05-26-2017

On inventory (yes/no)*

No

Yes